

TECHSPEC® Objectif pour Caméra Matricielle et Linéaire Série LS, 1,75X



1.75XLS Series Area Scan Lens

Stock #35-451 [CONTACT](#)

- 1 +

 €4.280,00

AJOUTER AU PANIER

Qté 1+

€4.280,00

Prix sur Quantité

[Demande de Devis](#)

ⓘ Les prix sont indiqués hors TVA et droits applicables.

Espace téléchargement

Champ de Vision, 28,7mm Capteur:
16.4mm

Option Iris:
Variable

Longueur (mm):
125.30

Diamètre Max. (mm):
75

Ouverture Numérique NA:

0.097
Max. Protrusion Derrière (mm): 0
Cercle Image Max. (mm): 82.00
Ouverture Numérique NA, Côté Objet: 0.0973
Champs de Vision Horizontal, Format de Capteur max.: 46.9mm
Champs de Vision Horizontal, Capteur de 35 mm: 20.6mm
Nombre d'Éléments (Groupes): 12 (7)
Remarque: Window is included. Length includes window. Specifications are at primary magnification.
Dia. de Monture (mm): 75
Taille de Capteur Optimale: 62.5mm
Type: Fixed Focal Length Lens
Distance Focale FL (mm): 99.00
Grossissement Primaire PMAG: 1.65X - 1.85X
Taille maximale du capteur: 82mm
Distance de Travail (mm): 62.60
Monture: V-70 Mbunt
Ouverture (f/#): f/3.2 - f/22
Traitement: 425 - 675 BBAR VIS
Spécification du Traitement: 425 - 675nm BBAR
Position de la Pupille d'Entrée (mm): 90.62
Plan Principal de l'Espace Objet (mm): 88.34
Plan Principal de l'Espace Image (mm): -79.41
Champs de Vision, Format de Capteur max.: Horizontal: 37.6mm - 13.2° Vertical: 28.2mm - 10° Diagonal: 47mm - 16.7°
Distorsion maximum (%): 0.05
Champ de Vision Horizontal, Capteur APS- H: 16.7mm
Field of View, 57.7mm Sensor : 33mm
Relative Illumination: >97%
Total Track (mm): 379.60
Field of View, 82mm Sensor: 46.9mm
Field of View, 62.5mm Sensor : 35.7mm
Beamsplitter / Line Scan: No
Position de la Pupille de Sortie (mm): -76.74
Lens Wavelength Range: VIS

Conformité réglementaire

RoHS: Conforme
Certificate of Conformance:

