

TECHSPEC®

Objectif pour Caméra Matricielle et Linéaire Série LS, 2,5X



2.5XLS Series Area Scan Lens

Stock **#35-453** [CONTACT](#)



1



€4.280,00

AJOUTER AU PANIER

Qté 1+

€4.280,00

Prix sur Quantité

[Demande de Devis](#)

ⓘ Les prix sont indiqués hors TVA et droits applicables.

Espace téléchargement

Champ de Vision, 28,7mm Capteur:
11.5mm

Option Iris:
Variable

Longueur (mm):
160.80

Diamètre Max. (mm):
75

Ouverture Numérique NA:

0.11
Max. Protrusion Derrière (mm): 0
Cercle Image Max. (mm): 82.00
Ouverture Numérique NA, Côté Objet: 0.1099
Champs de Vision Horizontal, Format de Capteur max.: 32.8mm
Champs de Vision Horizontal, Capteur de 35 mm: 14.4mm
Nombre d'Éléments (Groupes): 12 (7)
Remarque: Window is included. Length includes window. Specifications are at primary magnification.
Dia. de Monture (mm): 75
Taille de Capteur Optimale: 82mm
Type: Fixed Focal Length Lens
Distance Focale FL (mm): 117.00
Grossissement Primaire PMAG: 2.35X - 2.65X
Taille maximale du capteur: 82mm
Distance de Travail (mm): 59.40
Monture: V-70 Mbunt
Ouverture (f/#): f/2.9 - f/22
Traitement: 425 - 675 BBAR VIS
Spécification du Traitement: 425 - 675nm BBAR
Position de la Pupille d'Entrée (mm): 114.19
Plan Principal de l'Espace Objet (mm): 95.83
Plan Principal de l'Espace Image (mm): -77.27
Champs de Vision, Format de Capteur max.: Horizontal: 26.3mm - 8.1° Vertical: 19.7mm - 6.1° Diagonal: 32.9mm - 10°
Distorsion maximum (%): 0.01
Champ de Vision Horizontal, Capteur APS- H: 11.7mm
Field of View, 57.7mm Sensor : 23.1mm
Relative Illumination: >98%
Total Track (mm): 529.00
Field of View, 82mm Sensor: 32.8mm
Field of View, 62.5mm Sensor : 25mm
Beamsplitter / Line Scan: No
Position de la Pupille de Sortie (mm): -61.01
Lens Wavelength Range: VIS

Conformité réglementaire

RoHS: Conforme
Certificate of Conformance:

