

TECHSPEC® Objectif pour Caméra Linéaire Série LS 1,75X



LS Series Line Scan Lenses



Stock **#35-441** 3-4 JOURS

- 1 +

€4.280,00

AJOUTER AU PANIER

Qté 1+

€4.280,00

Prix sur Quantité

[Demande de Devis](#)

ⓘ Les prix sont indiqués hors TVA et droits applicables.

Espace téléchargement

Champ de Vision, 28,7mm Capteur:
16.4mm

Option Iris:
Variable

Longueur (mm):
122.00

Filetage Filtre:

M52 x 0.75
Diamètre Max. (mm): 95
Ouverture Numérique NA: 0.097
Poids (g): 1122
Max. Protrusion Derrière (mm): 0
Cercle Image Max. (mm): 82.00
Ouverture Numérique NA, Côté Objet: 0.0973
Champs de Vision Horizontal, Format de Capteur max.: 46.9mm
Course Totale Objectif (mm): 379.6
Nombre d'Éléments (Groupes): 12 (7)
Remarque: Beamsplitter is included. Length includes beamsplitter. Specifications are at primary magnification.
Dia. de Monture (mm): 75
Taille de Capteur Optimale: 62.5mm
Type: Line Scan
Distance Focale FL (mm): 99.00
Grossissement Primaire PMAG 1.65X - 1.85X
Taille maximale du capteur: 82mm
Distance de Travail (mm): 65.9
Monture: V-70 Mbunt
Ouverture (f/#): f/3.2 - f/22
Traitement: 425 - 675 BBAR VIS
Spécification du Traitement: 425 - 675nm BBAR
Position de la Pupille d'Entrée (mm): 90.62
Plan Principal de l'Espace Objet (mm): 88.34
Plan Principal de l'Espace Image (mm): -79.41
Champs de Vision, Format de Capteur max.: Diagonal: 47mm - 16.7°
Distorsion maximum (%): 0.05
Field of View, 57.7mm Sensor : 33mm
Relative Illumination: >97%
Total Track (mm): 379.60
Field of View, 82mm Sensor: 46.9mm
Field of View, 62.5mm Sensor : 35.7mm
Beamsplitter / Line Scan: Yes
Position de la Pupille de Sortie (mm): -76.74
Lens Wavelength Range: VIS

Conformité réglementaire

RoHS:
Conforme

Certificate of Conformance:
Visionner
