NOTES:

1. SUBSTRATE:
   FUSED SILICA MOUNTED IN BLACK ANODIZED ALUMINUM RING
2. TRNSMITTED WAVEFRONT ERROR: λ/4
3. RoHS: COMPLIANT

FOR INFORMATION ONLY:
DO NOT MANUFACTURE PARTS TO THIS DRAWING





SECTION A-A



BANDPASS FILTER

	VALUE
CENTER WAVELENGTH (CWL) (nm)	624 ± 3nm
MINIMUM BANDWIDTH (nm)	40
FULL WIDTH HALF MAX (FWHM) (nm)	46
MINIMUM TRANSMISSION (%)	>93
OD6 BLOCKING RANGE (nm)	445 - 595 & 663 - 818
SURFACE QUALITY	60-40
COATING TYPE	HARD COATED
DURABILITY	MIL-C-48479A, SECT. 3.4.1
ENVIRONMENTAL	MIL-STD-801F, SECT. 507 .4

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
DIMENSIONS ARE FOR REFERENCE ONLY

Edmund Optics®

THIRD ANGLE PROJECTION		TITLE	OD6, Ø50mm, 624nm x 40nm, BP FLUORESCENCE FILTER	
ALL DIMS IN	mm	DWG NO	67049	SHEET 1 OF 1