## NOTES:

1. SUBSTRATE:

FLOAT GLASS


2 F


FINE GROUND SURFACE


2 CANIDDI ACTED AT A 1

SANDBLASTED AT A 120 GRIT WITH TWO ORTHOGONAL PASSES

4. RoHS COMPLIANT







## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

|                  | \$1                  | \$2                  |           |  |  |
|------------------|----------------------|----------------------|-----------|--|--|
| SHAPE            | PLANO                | PLANO                | THI<br>PR |  |  |
| WAVELENGTH RANGE | 350 - 2000nm         | 350 - 2000nm         |           |  |  |
| BEVEL            | PROTECTIVE AS NEEDED | PROTECTIVE AS NEEDED | Α         |  |  |

|   | •                      |             |    |
|---|------------------------|-------------|----|
|   | THIRD ANGLE PROJECTION | $\phi \Box$ | TI |
| ) | ALL DIMS IN            | mm          | D  |

| B     | <b>Edmund Optics</b> ®          |
|-------|---------------------------------|
| TITLE | 16mm DIAMETER SANDBLASTED GLASS |

ALL DIMS IN mm DWG NO 43720 SHEET 1 OF 1