

NOTES:


- 1. SUBSTRATE: N-BK7
- 2. S2 TO BE PARALLEL WITH S1 TO <1 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: RAVG ≤1.75% @ 400 - 700nm



- 5. Rohs Compliant
- 6. SURFACE FLATNESS (P-V): $\lambda/4$ (per inch over clear aperture)







FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

S1 S2	
DI ANIO DI ANIO	
SHAPE PLANO PLANO	
SURFACE QUALITY 60-40 60-40	
CLEAR APERTURE Ø4.00 Ø4.00	
BEVEL PROTECTIVE AS NEEDED PROTECTIVE AS NE	EDED

THIRD ANGLE _ PROJECTION		TITLE	5mm D
ALL DIMS IN	mm	DWG NO	45574

5mm DIA., 2mm THICK, MGF2 COATED	λ/4
n-bk7 window	

Edmund Optics®

SHEET

1 OF 1