
NOTES:


1. SUBSTRATE: N-BK7


- 2. S2 TO BE PARALLEL WITH \$1 TO <1 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: RABS ≤0.25% @ 880nm RAVG ≤1.25% @ 400 - 870nm RAVG ≤1.25% @ 890 - 1000nm



- 5. Rohs Compliant
- 6. SURFACE FLATNESS (P-V): $\lambda/4$ (per inch over clear aperture)







45660

FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

\$1	
91	\$2
SHAPE PLANC	PLANO
SURFACE QUALITY 60-40	60-40
CLEAR APERTURE Ø18.00	0 Ø18.00
BEVEL PROTECTIVE AS	NEEDED PROTECTIVE AS NEEDED

_			
	THIRD ANGLE PROJECTION	ϕ	TITLE
	ALL DIMS IN	mm	DWG NO

Edmund Optics®
20mm DIA., 3mm THICK, VIS-NIR COATED λ/4 N-BK7 WINDOW

SHEET

1 OF 1