

NOTES:


- 1. SUBSTRATE: N-BK7
- 2. S2 TO BE PARALLEL WITH S1 TO <1 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) S1 & S2: R(AVG) ≤ 0.4% @ 425 - 675nm



- 5. Rohs Compliant
- 6. SURFACE FLATNESS (P-V): $\lambda/4$ (per inch over clear aperture)







PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2
SHAPE	PLANO	PLANO
SURFACE QUALITY	60-40	60-40
CLEAR APERTURE	Ø8.10	Ø8.10
BEVEL P	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

			Edmund Optics®	
HIRD ANGLE PROJECTION	\rightarrow	TITLE	9mm DIA., 2mm THICK, VIS 0° COATED N-BK7 WINDOW) λ/4
ALL DIMS IN	mm	DWG NO	49123	SHEET 1 OF

9n	nm DIA., 2mm THICK, VIS 0° COATED N-BK7 WINDOW	Ο λ/4
40	102	SHEET

1 OF 1