## NOTES:


- 1. SUBSTRATE MATERIAL: Fused Silica
- 2. SURFACE S2 TO BE PARALLEL WITH S1 TO 30 arcsec
- 3. COATING (APPLY ACROSS CLEAR APERTURE)


S1: Protected Silver R(avg) >98% @ 450 - 2000nm R(avg) >98% @ 2000 - 10,000nm


S2: NONE

4. FINE GRIND SURFACE

5. Rohs Compliant







## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	Edmund	Optics®
--	--------	---------

REV. A	\$1	\$2			10mm Course Protected Cilver Coated	\ /10
SURFACE QUALITY	20-10	COMMERCIAL POLISH	THIRD ANGLE PROJECTION	_ TITLE	10mm Square Protected Silver Coated, λ/10 Mirror	
SURFACE FLATNESS	λ/10	NA	'		WillOI	CUEET
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN mm	DWG NO	68324	SHEET 1 OF 1