NOTES:

1. SUBSTRATE: N-BK7


2. COATING (APPLY ACROSS CLEAR APERTURE)

S1: SILVER WITH PROTECTIVE OVERCOAT R(AVG) > 98% FROM 0.45-10.0 Microns @ 0° AOI


S2: NONE

3. FINE GRIND SURFACE


- 4. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- 5. ROHS COMPLIANT







SHEET 1 OF 1



SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2
SHAPE	CONVEX	PLANO
RADIUS	800mm	N/A
SURFACE QUALITY	60-40	N/A
FOCAL LENGTH TOLERANCE	±2%	N/A
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

		81	Edmund Optic	S®
THIRD ANGLE - PROJECTION	$\phi \lhd$	TITLE	Ø50mm, -400mm FL PROTECTED SILV CONVEX MIRROR	ER,
ALL DIMS IN	mm	DWG NO	87687	SHEET 1 OF