NOTES:

- SUBSTRATE MATERIAL: N-BK7
- 2. COATING (APPLY ACROSS CLEAR APERTURE)


S1 & S2: LASER V-COAT


R(abs) <0.25% @ 1064nm

3. FINE GROUND SURFACE

4. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICAIONS APPLY ACROSS CLEAR APERTURE

5. RoHS COMPLIANT







FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

		DIMENSIONS ARE FOR REFERENCE ONLY					
	S1	S2					
SHAPE	CONVEX	PLANO	EFL	25±3%		Edmund Ontic	N R
RADIUS	12.96	∞	BFL	(23.09)		Edmund Optic	5S°
SURFACE QUALITY	60-40	60-40			TITLE	12.5mm DIA X 25.0mm FL 1064nm V-COAT, CYLINDER LENS	
CLEAR APERTURE	Ø11.50	Ø11.50					
COATING APERTURE	Ø11.50	Ø11.50		1			CUEET
BEVEL	PROTECTED AS NEEDED	PROTECTED AS NEEDED	ALL DIMS IN	mm	DWG NO	33231	SHEET 1 OF 1

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY