NOTES:

SUBSTRATE MATERIAL:
FUSED SILICA

2. COATING (APPLY ACROSS CLEAR APERTURE)


\$1 & \$2: NONE


3. WEDGE TOLERANCE: <15 arcmin




5. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICAIONS APPLY ACROSS CLEAR APERTURE

6. Rohs Compliant







FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

REV. A	S1	S2				
SHAPE	CONVEX	PLANO	EFL	25		Edmund Ontion
RADIUS	11.46	∞	BFL	22.94	Ul	Edmund Optics®
SURFACE QUALITY	40-20	40-20		1		12.5mm DIAMETER X 25mm FL UNCOATED, UV
CLEAR APERTURE	Ø11.50	Ø11.50	THIRD ANGLE PROJECTION	\bigcirc	TITLE	PCX CYLINDER LENS
COATING APERTURE	Ø11.50	Ø11.50		I		
BEVEL	PROTECTED AS NEEDED	PROTECTED AS NEEDED	ALL DIMS IN	mm	DWG NO	68168 SHEET 1 OF 1