


NOTES:


1. SUBSTRATE:
CELLULOSE TRIACETATE (TAC)
2. COATING
UNCOATED, PROTECTIVE FILM ON BOTH SIDES
3. POLARIZATION (%):
99.83 @ 400 - 760nm
99.63 @ 761 - 2200nm
4. TRANSMISSION (%):
SINGLE:
29 @ 400 - 760nm
39 @ 761 - 2200nm

CROSSED:
0.02 @ 400 - 760nm
0.11 @ 761 - 2200nm
5. EXTINCTION RATIO: 400:1 (average @ 800-2200 nm)
6. WAVELENGTH RANGE: 400 - 2200nm
7. POLARIZATION AXIS LABEL IS ON SUBSTRATE MASKING
8. ROHS COMPLIANT



**FOR INFORMATION ONLY:
DO NOT MANUFACTURE
PARTS TO THIS DRAWING**

SPECIFICATIONS SUBJECT TO
CHANGE WITHOUT NOTICE
DIMENSIONS ARE FOR
REFERENCE ONLY

 Edmund Optics®			
THIRD ANGLE PROJECTION 		TITLE	50 x 50mm NIR Linear Polarizing Film
ALL DIMS IN	mm	DWG NO	12474
			SHEET 1 OF 1