



<b>→</b>	- 5.00±0.10


	VALUE
CENTER WAVELENGTH (nm)	400nm
FULL WIDTH HALF MAX (nm)	10nm
MINIMUM TRANSMISSION	≥85
BLOCKING	200 - 1200
SURFACE QUALITY	80-50
CONSTRUCTION	MOUNTED IN BLACK ANODIZED ALUMINUM RING
COATING TYPE	HARD COATED

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

				Edmund Optic	S®
	THIRD ANGLE _ PROJECTION		TITLE	OD4, Ø25mm, 400nm x 10nm, HC, BP	FILTER
_	ALL DIMS IN	mm	DWG NO	65132	SHEET 1 OF 1









- 5.00±0.10


	VALUE
CENTER WAVELENGTH (nm)	450nm
FULL WIDTH HALF MAX (nm)	10nm
MINIMUM TRANSMISSION	≥85
BLOCKING	200 - 1200
SURFACE QUALITY	80-50
CONSTRUCTION	MOUNTED IN BLACK ANODIZED ALUMINUM RING
COATING TYPE	HARD COATED

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

				Edmund Optic	S®
	THIRD ANGLE PROJECTION		TITLE	OD4, Ø25mm, 450nm x 10nm, HC, BP	FILTER
_	ALL DIMS IN	mm	DWG NO	65140	SHEET 1 OF 1








<b>→</b>	- 5.00±0.10


	VALUE
CENTER WAVELENGTH (nm)	500nm
FULL WIDTH HALF MAX (nm)	10nm
MINIMUM TRANSMISSION	≥85
BLOCKING	200 - 1200
SURFACE QUALITY	80-50
CONSTRUCTION	MOUNTED IN BLACK ANODIZED ALUMINUM RING
COATING TYPE	HARD COATED


SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

			Edmund Optic	S®
 THIRD ANGLE PROJECTION	$\phi \Box$	TITLE	OD4, Ø25mm, 500nm x 10nm, HC, BP	FILTER
 ALL DIMS IN	mm	DWG NO	65149	SHEET 1 OF 1

® \_\_\_\_









<b>→</b>	- 5.00±0.10


	VALUE
CENTER WAVELENGTH (nm)	550nm
FULL WIDTH HALF MAX (nm)	10nm
MINIMUM TRANSMISSION	≥85
BLOCKING	200 - 1200
SURFACE QUALITY	80-50
CONSTRUCTION	MOUNTED IN BLACK ANODIZED ALUMINUM RING
COATING TYPE	HARD COATED

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

				Edmund Option	;S®
_	THIRD ANGLE PROJECTION		TITLE	OD4, Ø25mm, 550nm x 10nm, HC, BP	FILTER
_	ALL DIMS IN	mm	DWG NO	65159	SHEET 1 OF 1









<b>→</b>	- 5.00±0.10


	VALUE
CENTER WAVELENGTH (nm)	600nm
FULL WIDTH HALF MAX (nm)	10nm
MINIMUM TRANSMISSION	≥85
BLOCKING	200 - 1200
SURFACE QUALITY	80-50
CONSTRUCTION	MOUNTED IN BLACK ANODIZED ALUMINUM RING
COATING TYPE HARD COATED	

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

				Edmund Optic	S®
	THIRD ANGLE PROJECTION	$\phi$	TITLE	OD4, Ø25mm, 600nm x 10nm, HC, BP	FILTER
_	ALL DIMS IN	mm	DWG NO	65163	SHEET 1 OF 1









-	5.00±0.10


	VALUE
CENTER WAVELENGTH (nm)	650nm
FULL WIDTH HALF MAX (nm)	10nm
MINIMUM TRANSMISSION	≥85
BLOCKING	200 - 1200
SURFACE QUALITY 80-50	
CONSTRUCTION	MOUNTED IN BLACK ANODIZED ALUMINUM RING
COATING TYPE	HARD COATED

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

				Edmund Optic	S®
	THIRD ANGLE PROJECTION		TITLE	OD4, Ø25mm, 650nm x 10nm, HC, BP	FILTER
_	ALL DIMS IN	mm	DWG NO	65170	SHEET 1 OF 1







-	<del></del>	— 5.	00±0.	10
_				

	VALUE
CENTER WAVELENGTH (nm)	700nm
FULL WIDTH HALF MAX (nm)	10nm
MINIMUM TRANSMISSION	>85
BLOCKING	200 - 1200
SURFACE QUALITY	80-50
CONSTRUCTION	MOUNTED IN BLACK ANODIZED ALUMINUM RING
COATING TYPE HARD COATED	

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

				Edmund Optic	S®
_	THIRD ANGLE PROJECTION		TITLE	OD4, Ø25mm, 700nm x 10nm, HC, BP	FILTER
_	ALL DIMS IN	mm	DWG NO	88012	SHEET 1 OF 1