NOTES:

- 1. SUBSTRATE: N-BK7
- 2. S2 TO BE PARALLEL WITH S1 TO < 1ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE)

S1 & S2: R(ABS) ≤0.25% @ 880nm

R(AVG) ≤1.25% @ 400 - 870nm


R(AVG) ≤1.25% @ 890 - 1000nm





4. FINE GRIND SURFACE

5. Rohs Compliant

6. SURFACE FLATNESS (P-V): λ/4 (per inch over clear aperture)







FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2	
SHAPE	PLANO	PLANO	
SURFACE QUALITY	60-40	60-40	
CLEAR APERTURE (mm)	Ø22.86	Ø22.86	
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	

THIRD ANGLE PROJECTION	\rightarrow	TITLE
ALL DIMS IN	mm	DWG NO

	Edmund Optics®
TITLE	25.4mm DIA., 2mm THICK, VIS-NIR COATED
	\ /4 NLDV7 \\/\ID\\/\/\

			7,411 810 11118011	
ll DIMS IN	mm	DWG NO	15436	SHEET