
## NOTES:

1. SUBSTRATE:

HOYA GLASS: ND-50

2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO WITHIN < 0.02mm


FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING




3. FINE GRIND SURFACE

4. COATING SPECIFICATION: S1 & S2:R(AVG) ≤0.4% @ 425 - 675nm

- 5. OPTICAL DENSITY: 0.3 +/-0.05 @400-700nm
- 6. TRANSMISSION (%): 50.0% AVERAGE FROM 400-700nm
- 7. ROHS COMPLIANT





T

A

NEUTRAL DENSITY FILTER

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY



	S1	S2	1	TITLE	0.3 OD, 50mm DIA., VIS 0° COATED, ABSORPTIVE ND FILTER		
SHAPE	PLANO	PLANO	THIRD ANGLE PROJECTION				
SURFACE QUALITY	80-50	80-50		I		, , , , , , , , , , , , , , , , , , , ,	CLIEFT
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	13115	SHEET 1 OF 1