
NOTES:


- 1. SUBSTRATE MATERIAL: FUSED SILICA
- 2. ONLY ROHS-COMPLIANT MATERIALS ARE ACCEPTABLE.

 DO NOT SUBSTITUTE WITH ROHS EXEMPT OR NONCOMPLIANT MATERIALS
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1& \$2 : UNCOATED



- 5. POWER, IRREGULARITY, AND SURFACE QUALITY
 SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- 6. CHIPS OUTSIDE OF CLEAR APERTURE: <0.5
- 7. CLEAR APERTURE AND COATING APERTURE ARE CENTERED ON SURFACES





FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

SHEET 1 OF 1

SHAPE	S1 & S2 PLANO				Edmund Optic	\ /\
SURFACE QUALITY SURFACE FLATNESS	20-10 λ/10	THIRD ANGLE PROJECTION	$\hspace{1cm} \hspace{1cm} \hspace{1cm}\hspace{1cm}\hspace{1cm}\hspace{1cm}\hspace{1cm}\hspace{1cm}\hspace{1cm}\hspace{1cm}\hspace{1cm}\hspace{1cm}\hspace{1cm}1c$	TITLE	25mm Dia., Uncoated, 8° Fused Silica Wedged Window	
CLEAR APERTURE	Ø22.50				- reages masen	_
BEVEL	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	25672	L