## NOTES:

1. SUBSTRATE:

FUSED SILICA (CORNING 7980)

## 2. S1 TO BE PARALLEL WITH S1 TO WITHIN <1 ARCMIN

3. COATING (APPLY ACROSS CLEAR APERTURE)

S1 & S2: UV-AR (250-425nm)


R(ABS) ≤1.0% @ 250 - 425nm


R(AVG) ≤0.75% @ 250 - 425nm

R(AVG) ≤0.5% @ 370 - 420nm

4. FINE GRIND SURFACE

5. ROHS COMPLIANT





## PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

SHEET

1 OF 84

	\$1	\$2
SHAPE	PLANO	PLANO
SURFACE QUALITY	40 - 20	40 - 20
CLEAR APERTURE	Ø9.00	Ø9.00
BEVEL	PROTECTED AS NEEDED	PROTECTED AS NEEDED

			Edmund Option	S®
THIRD ANGLE PROJECTION	<b>\rightarrow</b>	TITLE	10mm Dia., 3mm Thick, UV-AR Coated Fused Silica Window	Ι, λ/4
ALL DIMS IN	mm	DWG NO	72335	SHEE 1 OF