

## Solid State UV Flood Light Systems (Recertified 05-P)



Solid State UV Flood Light Systems

Stock #16-762-RCD-05P **RECERTIFIÉ** 1 In Stock

⊖ 1 ⊕ €2.250<sup>00</sup>

**AJOUTER AU PANIER**

Prix sur Quantité	
Qté 1+	€2.250,00 prix unitaire
Need More?	<a href="#">Demande de Devis</a>

ⓘ Les prix sont indiqués hors TVA et droits applicables.

Espace téléchargement

### Caractéristiques du produit

**Durée de Vie d'Utilisation (heures):**  
>20,000

### Propriétés physiques et mécaniques

**Dimensions (mm):**  
UV Curing Head: 55 x 52 x 148  
Control Box 160 x 150 x 80

### Propriétés optiques

**Longueur d'Onde (nm):**

380.00 ±5

**Beam Size (mm):**

50 x 50mm (30mm WD)  
100 x 100mm (100mm WD)

**Distance de Travail (mm):**

30 - 100

**Irradiance (W/cm<sup>2</sup>):**

0.8

## Connectivité matérielle & interfaçage

**Alimentation:**

AC 100 - 240V

## Conformité réglementaire

**Certificate of Conformance:**

[Visionner](#)

## Description produit

- Large, Uniform UV Light Output
- 380nm Center Wavelength
- Up to 0.8W/cm<sup>2</sup> UV Irradiance

Solid State UV Flood Light Systems produce a large, uniform output beam of UV light centered at 380nm. These systems consist of a controller box with a built-in timer for automated curing and a handheld UV flood light with an on-off switch. The controller box features integrated heat sinks and a cooling fan, allowing for continuous operation without a change in UV intensity. Solid State UV Flood Light Systems are ideal for UV curing applications, especially those with either large components or multiple small components to cure.