

Solid State UV Flood Light Systems (Recertified 05-P)



Solid State UVFlood Light Systems

Stock #16-762-RCD-05P

RECERTIFIÉ

1 In Stock

-

1

+

€2.250⁰⁰

AJOUTER AU PANIER

Prix sur Quantité	
Qté 1+	€2.250,00 prix unitaire
Need More?	Demande de Devis

Les prix sont indiqués hors TVA et droits applicables.

Espace téléchargement

Caractéristiques du produit

Durée de Vie d'Utilisation (heures):

>20,000

Propriétés physiques et mécaniques

Dimensions (mm):

UV Curing Head: 55 x 52 x 148
Control Box 160 x 150 x 80

Propriétés optiques

Longueur d'Onde (nm):

380.00 ±5	
50 x 50mm (30mm WD) 100 x 100mm (100mm WD)	Beam Size (mm):
30 - 100	Distance de Travail (mm):
0.8	Irradiance (W/cm²):
Connectivité matérielle & interfaçage	
AC 100 - 240V	Alimentation:
Conformité réglementaire	
Visionner	Certificate of Conformance:

Description produit

- Large, Uniform UV Light Output
- 380nm Center Wavelength
- Up to 0.8W/cm² UV Irradiance

Solid State UV Flood Light Systems produce a large, uniform output beam of UV light centered at 380nm. These systems consist of a controller box with a built-in timer for automated curing and a handheld UV flood light with an on-off switch. The controller box features integrated heat sinks and a cooling fan, allowing for continuous operation without a change in UV intensity. Solid State UV Flood Light Systems are ideal for UV curing applications, especially those with either large components or multiple small components to cure.